FIIG A516V

Reprint Date: September 4, 2009

FEDERAL ITEM IDENTIFICATION GUIDE CABINET, FOOD WARMING, STEAM HEATED ITEM NAME CODE 16743

This Reprint replaces FIIG A516V, dated January 6, 2006.



Commander

Defense Logistics Information Service

ATTN: DLIS-K

74 Washington Avenue North, Suite 7

Battle Creek, Michigan 49037-3084

(COMM) (269) 961-5779

(DSN) 661-5779

This Federal Item Identification Guide for Supply Cataloging is issued under the authority of Department of Defense Instruction 5025.7.

The use of this publication is mandatory for US. Federal Activities participating in Federal Catalog System Operations.

BY ORDER OF THE DIRECTOR

/s/

Commander

Defense Logistics Information Service

Table of Contents

SECTION I	1
Reply Tables	10
Reference Drawing Groups	14
FIIG Change List	15

SECTION I

MRC Mode Code Requirements

NAME **ITEM NAME** D

> Definition: A NOUN, WITH OR WITHOUT MODIFIERS, BY WHICH AN ITEM OF SUPPLY IS KNOWN.

Reply Instructions: Enter the Item Name Code. (e.g., NAMED16743*)

CYGG * D **CABINET MATERIAL**

> Definition: THE CHEMICAL COMPOUND OR MECHANICAL MIXTURE PROPERTIES OF WHICH THE CABINET IS FABRICATED.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., CYGGDSTA000*; CYGGDSTA000\$\$DSTB000*)

> REPLY CODE REPLY (MA01) ALA000 ALUMINUM STEEL STA000

STEEL CORROSION RESISTING STB000 Steel Stainless (use Reply Code STB000)

ABFY J OVERALL DEPTH

Definition: AN OVERALL MEASUREMENT BETWEEN SPECIFIED POINTS OF AN ITEM. IN DISTINCTION FROM HEIGHT

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABFYJAA20.000*; ABFYJLA927.0*; ABFYJAB18.000\$\$JAC22.000*)

Table 1

REPLY CODE REPLY (AA05) **INCHES**

L **MILLIMETERS**

Table 2

REPLY CODE REPLY (AC20) **NOMINAL** В **MINIMUM** C **MAXIMUM**

MRC Mode Code Requirements

ABMK J OVERALL WIDTH

Definition: AN OVERALL MEASUREMENT TAKEN AT RIGHT ANGLES TO THE LENGTH OF AN ITEM, IN DISTINCTION FROM THICKNESS.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABMKJAA9.000*; ABMKJLA75.0*; ABMKJAB7.000\$\$JAC10.000*)

Table 1

REPLY CODE
A INCHES
L MILLIMETERS

Table 2

REPLY CODE
A NOMINAL
B MINIMUM
C MAXIMUM

ABKW J OVERALL HEIGHT

Definition: THE DISTANCE MEASURED IN A STRAIGHT LINE FROM THE BOTTOM TO THE TOP OF AN ITEM.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABKWJAA70.000*; ABKWJLA700.0*; ABKWJAB60.000\$\$JAC70.000*)

Table 1

REPLY CODE A INCHES
L MILLIMETERS

Table 2

REPLY CODE
A NOMINAL
B MINIMUM
C MAXIMUM

ACDC D CURRENT TYPE

MRC Mode Code Requirements

Definition: INDICATES THE TYPE OF CURRENT WHETHER ALTERNATING, DIRECT, OR BOTH.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., ACDCDB*)

REPLY CODE	REPLY (AB62)
В	AC
D	AC/DC
C	DC

AMSE J VOLTAGE RATING

Definition: THE VALUE(S) OF POTENTIAL FOR WHICH THE ITEM IS RATED.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., AMSEJVA110.0*; AMSEJVB115.0\$\$JVC120.0*)

Table 1	
REPLY CODE	REPLY (AB63)
K	KILOVOLTS
V	VOLTS

Table 2	
REPLY CODE	REPLY (AC20)
A	NOMINAL
В	MINIMUM
C	MAXIMUM

FAAZ * D PHASE

Definition: THE NUMBER OF ALTERNATING CURRENT PHASES.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., FAAZDA*)

REPLY CODE	<u>REPLY (AD02)</u>
A	SINGLE
E	SINGLE/THREE
C	THREE
В	TWO

MRC Mode Code Requirements

BDWW * J WATTAGE RATING

Definition: THE RATED POWER THAT AN ITEM CAN SAFELY CONSUME OR PROVIDE.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric value. (e.g., BDWWJAT40.0*; BDWWJBC2.0\$\$JBC2.1*;

REPLY CODE REPLY (AB49)
BC KILOWATTS
AT WATTS

APNB * J AC FREQUENCY RATING

Definition: THE NUMBER OF COMPLETE ALTERNATING CURRENT CYCLIC CHANGES, PER UNIT OF TIME, FOR WHICH THE ITEM IS RATED.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., APNBJEA60.0*; APNBJEB50.0\$\$JEC60.0*)

 Table 1

 REPLY CODE
 REPLY (AC32)

 E
 HERTZ

 K
 KILOHERTZ

Table 2

REPLY CODE
A NOMINAL
B MINIMUM
C MAXIMUM

BGYT * A ADJUSTABLE SHELF QUANTITY

Definition: THE NUMBER OF ADJUSTABLE SHELVES PROVIDED WITH THE ITEM.

Reply Instructions: Enter the quantity. (e.g., BGYTA2*)

BGYS * A FIXED SHELF QUANTITY

Definition: THE NUMBER OF FIXED SHELVES PROVIDED WITH THE ITEM.

MRC Mode Code Requirements

Reply Instructions: Enter the quantity. (e.g., BGYSA2*)

BCBP A DRAWER QUANTITY

Definition: THE NUMBER OF DRAWERS PROVIDED.

Reply Instructions: Enter the quantity. (e.g., BCBPA18*)

AFPV * Α **COMPARTMENT QUANTITY**

Definition: THE NUMBER OF COMPARTMENTS FORMED BY PARTITIONS.

Reply Instructions: Enter the quantity. (e.g., AFPVA84*)

AAXX MOUNTING TYPE D

Definition: INDICATES THE TYPE OF MOUNT UTILIZED TO SUPPORT THE

ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g.,

AAXXDABE*)

REPLY CODE REPLY (AA78) **COUNTER ABE ACF FLOOR AFU** LEG(S)

RIGID CASTER **AFP SWIVEL CASTER AFR**

ABJJ HEATED DRAWER QUANTITY A

Definition: THE NUMBER OF DRAWERS THAT ARE ELECTRICALLY

HEATED.

Reply Instructions: Enter the quantity. (e. g., ABJJA2*)

BDWT D **HEATING METHOD**

Definition: THE MEANS BY WHICH THE ITEM IS HEATED.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g.,

BDWTDAR*)

REPLY CODE REPLY (AM63) **ELECTRICALLY** AF AR

STEAM

MRC Mode Code Requirements

AKYD * G ACCESSORY COMPONENTS AND QUANTITY

Definition: THE NAME AND NUMBER OF PARTS SUPPLIED WITH THE ITEM WHICH MAY BE REQUIRED FOR APPLICATION.

Reply Instructions: Enter the reply in clear text. (e.g., AKYDGONE SET OF CASTERS*)

FEAT * G SPECIAL FEATURES

Definition: THOSE UNUSUAL OR UNIQUE CHARACTERISTICS OR QUALITIES OF AN ITEM NOT COVERED IN THE OTHER REQUIREMENTS AND WHICH ARE DETERMINED TO BE ESSENTIAL FOR IDENTIFICATION.

Reply Instructions: Enter the reply in clear text. (e.g., FEATGQUALITY CONTROLLED*)

ZZZK * J SPECIFICATION/STANDARD DATA

Definition: THE DOCUMENT DESIGNATOR OF THE SPECIFICATION OR STANDARD WHICH ESTABLISHED THE ITEM OF SUPPLY.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the Commercial and Government Entity (CAGE) Code of the entity controlling the document, a dash, and the document designator. The agency that controls the limited coordination document must be preceded and followed by a slash following the designator. The word canceled or superseded must be preceded and followed by a slash for the designator. Professional and industrial association specifications/standards are differentiated from a manufacturer's specification in that the data has been coordinated and published by the professional and industrial association. Include amendments and revisions where applicable.

(e.g., ZZZKJT81337-30642B*;

ZZZKJS81349-MIL-D-180 REV1/CANCELED/*;

ZZZKJP80205-NAS1103*;

ZZZKJS81349-MIL-C-1140C/CE/*;

ZZZKJT81337-30642B\$\$JP80205-NAS1103*)

REPLY (AN62)

MRC	Mode Code	Requirements
	CC	<u>DDE</u>
	S	GOVERNMENT SPECIFICATION
	T	GOVERNMENT STANDARD
	D	MANUFACTURERS SOURCE CONTROL
	R	MANUFACTURERS SPECIFICATION
	N	MANUFACTURERS SPECIFICATION CONTROL
	M	MANUFACTURERS STANDARD
	В	NATIONAL STANDARD/SPECIFICATION
	A	PROFESSIONAL/INDUSTRIAL ASSOCIATION
		SPECIFICATION
	P	PROFESSIONAL/INDUSTRIAL ASSOCIATION
		STANDARD

ZZZT * J NONDEFINITIVE SPEC/STD DATA

NOTE: If the specification/standard cited in reply to MRC ZZZK is nondefinitive, reply to MRC ZZZT. This reply is the data which is not recorded in Segment C.

Definition: THE NUMBER, LETTER, OR SYMBOL THAT INDICATES THE TYPE, STYLE, GRADE, CLASS, AND THE LIKE, OF AN ITEM IN A NONIDENTIFYING SPECIFICATION OR STANDARD.

Reply Instructions: Enter the applicable Reply Code from <u>Appendix A</u>, Table 1, followed by the appropriate number, letter, or symbol. (e.g., ZZZTJTY1*; ZZZTJTY1\$\$JSTA*; ZZZTJTY1\$JSTA*)

ZZZY * G REFERENCE NUMBER DIFFERENTIATING CHARACTERISTICS

Definition: A FEATURE OF THE ITEM OF SUPPLY WHICH MUST BE SPECIFICALLY RECORDED WHEN THE REFERENCE NUMBER COVERS A RANGE OF ITEMS.

Reply Instructions: Enter the reply in clear text. (e.g., ZZZYGCOLOR CODED LEADS*; ZZZYGAS DIFFERENTIATED BY MATERIAL*)

CRTL * A CRITICALITY CODE JUSTIFICATION

Definition: THE MASTER REQUIREMENT CODES OF THOSE REQUIREMENTS WHICH ARE TECHNICALLY CRITICAL BY REASON OF TOLERANCE, FIT, PERFORMANCE, OR OTHER CHARACTERISTICS WHICH AFFECT IDENTIFICATION OF THE ITEM.

Reply Instructions: Enter the Master Requirement Code for the requirement, the reply to which renders the item as being critical. (e.g., CRTLAAKJA*; CRTLAAKJA\$\$ACSGS*)

MRC Mode Code Requirements

Reply to this requirement only if the header record for the item identification for the item being identified has been coded as critical.

PRPY * A PROPRIETARY CHARACTERISTICS

NOTE: If Document Availability Code B, D, F, or H, reply to MRC PRPY.

Definition: IDENTIFICATION OF THOSE CHARACTERISTICS INCLUDED IN THE DESCRIPTION FOR WHICH A NON-GOVERNMENT ACTIVITY HAS IDENTIFIED ALL OR SELECTED CHARACTERISTICS OF THE ITEM AS BEING PROPRIETARY AND THEREFORE RESTRICTED FROM RELEASE OUTSIDE THE GOVERNMENT WITHOUT PRIOR PERMISSION OF THE ORIGINATOR OF THE DATA.

Reply Instructions: Enter the MRC codes of the individual characteristics of the description which are marked proprietary on the technical data, using AND coding (\$\$) for multiple characteristics. If all the MRCs are proprietary, enter the reply PACS. If none of the MRCs is proprietary, enter the reply NPAC. (e.g., PRPYAPACS*; PRPYANPAC*; PRPYAAKJA\$\$ACSGS*)

ELRN * G EXTRA LONG REFERENCE NUMBER

Definition: A REFERENCE NUMBER EXCEEDING 32 POSITIONS.

Reply Instructions: Enter the entire reference number. Do not include the 5-position Commercial and Government Entity (CAGE) Code unless there is more than one extra long reference number on the NSN, (e.g., ELRNGANN112036BIL060557LEN313605UZ62365*).

If there is more than one extra long reference number on the NSN, include the CAGE or NCAGE and separate each reference by using the "&" character, (e.g., 28480 ANN112036BIL060557LEN313605UZ62365 & S1234 NN112036BIL060557LEN313605UZ62365).

In determining quantity of characters in the reference number, count will be made after modification in accordance with Volume 2, Chapter 9, FLIS Procedures Manual, DoD 4100.39-M.

ENAC * D ENVIRONMENTAL ATTRIBUTE CODE

NOTE: Answering this MRC will generate an ENAC Code in the Item Identification Segment (A) of the NSN.

MRC Mode Code Requirements

Definition: INDICATES THE TYPE OF PRODUCT THAT MEETS OR EXCEEDS THE GOVERNMENT GUIDELINES FOR ENVIRONMENTALLY PREFERRED CHARACTERISTICS.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., ENACDJP*)

<u>REPLY</u>	REPLY (EN02)
CODE	
HD	ENERGY EFFICIENT – ENERGY STAR –
	COMMERCIAL FOOD SERVICE – COMMERCIAL HOT
	FOOD HOLDING CABINETS
JP	ENERGY EFFICIENT – FEMP- FOOD SERVICE
	EQUIPMENT – HOT FOOD HOLDING CABINETS
NR	REVIEWED – DOES NOT MEET SOME ENAC
	CRITERIA

CLQL* G COLLOQUIAL NAME

Definition: A COMMON USAGE NAME BY WHICH AN ITEM IS KNOWN.

Reply Instructions: Enter the reply in clear text. (e.g., CLQLGWOVEN WIRE CLOTH*)

AGAV * G END ITEM IDENTIFICATION

Definition: THE NATIONAL STOCK NUMBER OR THE IDENTIFICATION INFORMATION OF THE END EQUIPMENT FOR WHICH THE ITEM IS A PART.

Reply Instructions: Enter the applicable reply in clear text.

(e.g., AGAVG3930-00-000-0000*;

AGAVGFORKLIFT TRUCK, SMITH CORPORATION, MODEL 12, TYPE A*)

Reply Tables

Table 1 - NONDEFINITIVE SPEC/STD DATA NONDEFINITIVE SPEC/STD DATA

DEDI V CODE	DEDLY (ADOS)
REPLY CODE AL	REPLY (AD08) ALLOY
AL AN	ANNEX
AP	APPENDIX
AC	APPLICABILITY CLASS
AR	ARRANGEMENT
AS	ASSEMBLY
AB	ASSORTMENT
BX	BOX
CY	CAPACITY
CA	CASE
CT	CATEGORY
CL	CLASS
CE	CODE
CR	COLOR
CC	COMBINATION CODE
CN	COMPONENT
CP	COMPOSITION
CM	COMPOUND
CD	CONDITION
CS	CONSTRUCTION
DE	DESIGN
DG	DESIGNATOR
DW	DRAWING NUMBER
EG	EDGE
EN	END
FY	FAMILY
FG	FIGURE
FN	FINISH
FM	FORM
FA	FORMULA
GR	GRADE
GP	GROUP
BA	IMAGE COLOR
NS	INSERT
TM	ITEM
KD	KIND
KT	KIT
LG	LENGTH
LT	LIMIT
MK	MARK
AA	MARKER
ML	MATERIAL

REPLY CODE REPLY (AD08)

BB MAXIMUM DENSITY

MH MESH ME METHOD

BC MINIMUM DENSITY

MD MODEL
MT MOUNTING
NR NUMBER
PT PART
PN PATTERN

PC PHYSICAL CONDITION

PS PIECE
PL PLAN
PR POINT
QA QUALITY
RN RANGE
RT RATING

RF REFERENCE NUMBER

SC SCHEDULE SB **SECTION** SL**SELECTION** SE **SERIES** SV **SERVICE** SXSET SA **SHADE** SH **SHAPE** SG **SHEET** SZSIZE PZ**SPECIES**

SQ SPECIFICATION SHEET

SD SPEED
ST STYLE
SS SUBCLASS
SF SUBFORM
SP SUBTYPE

SN SURFACE CONDITION

SY**SYMBOL** SM **SYSTEM** TB **TABLE** TN **TANNAGE** TP **TEMPER** TX**TEXTURE** ΤK **THICKNESS** TT **TREATMENT**

TR TRIM
TY TYPE
YN UNIT

REPLY CODE	REPLY (AD08)
VA	VARIETY
WT	WEIGHT
WD	WIDTH

Reference Drawing Groups

No table of contents entries found.

FIIG Change List

FIIG Change List, Effective September 4, 2009

Revised Reply for Reply Code JP, and added reply codes HD and NR to MRC ENAC.